



Pro Seal Brite

CONCENTRATED FLOOR SEALER

FLOOR CARE PRODUCTS

DESCRIPTION: PRIDE'S PRO SEAL BRITE is an excellent sealer base and undercoat recommended for high traffic or worn areas. Use prior to the first application of PRIDE'S GLOSS PRO I or II. PRO SEAL BRITE closes pores and provides a clear, long – lasting hard surface for all types of resilient floors such as: vinyl, rubber, linoleum and terrazzo. This product contains nonconverting polymers.

DIRECTIONS:

- To prepare floor, thoroughly strip floor with PRIDE'S PRO WAXX AWAY to remove all old wax build – up. Rinse floor with clean water. Repeat rinse cycle to totally neutralize and remove any residual stripper.
- To start application of PRIDE'S PRO SEAL BRITE, floor must completely dry and clean. Apply a thin first coat using a clean mop using light even strokes across floor without scrubbing motion.
- Allow a minimum of 30 minutes drying time; longer in hot, humid weather.
- Be sure first coat is completely dry before application of a second coat using the same procedure as the first coat.
- NOTE: Both coatings should be thin, not thick, even coats. Do not attempt to touch up missed spots until floor is dry.

PACKAGING:

SIZE
 4/1 gallon case
 5 gallon pail

CATALOG #
 64600304
 64600305

PRODUCT SPECIFICATIONS

Appearance: Milky Liquid
 Color: White
 Odor: Characteristic
 pH: 8.0 - 9.0
 Specific Gravity: 1.010 - 1.030
 Viscosity: <10
 Solid Content: 14.7%

Detergent resistant to MULTI-PURPOSE CLEANER at 2.5 oz./ gal. dilution applied on vinyl black composite tile: Less than 10% deterioration after 60 strokes (ASTM 3207-73).
 Accelerated aging @ 52° Condition after 30 days: No separation, gelling or creaming (ASTM 1791-82).

ISO 9001:2000 Certified
 Certificate No. 2049



EAGLE Registrations Inc.
 SERVICE • INTEGRITY • VALUE

PRIDE ENTERPRISES
 P. O. Box 1425 Avon Park, FL 33826
 Phone: 813-890-6594 Fax: 813-890-2101 www.pride-enterprises.org



CONTROLLED

Issue Date: 05/09/08
 Form PB646003, Rev (G)

MATERIAL SAFETY DATA SHEET

Prepared By: D. Wilson

(Prepared According to 29 CFR 1910.1200)

Effective Date: 08/10/05

SECTION 1- PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: PRO SEAL BRITE
Generic Name: Acrylic Floor Finish
Product Group: Floor Care Products

Manufacturer's Name: SANITARY MAINTENANCE & SUPPLY
 P.O. BOX 1425
 AVON PARK, FL 33826
Phone #: (813)-890-6594

SECTION 2- INGREDIENT INFORMATION

CHEMICAL NAME	CAS #	WT %	PEL	TWA-TLV	STEL-TLV
Diethylene Glycol Methyl Ether	111-77-3	<2	N.A.	10/ m ³	N.A.
Dibutyl Phthalate	N/A	>3	N/A.	N/A.	N/A.
Formaldehyde	N/A	>.001	N/A.	N/A.	N/A.

No Components, in excess of 0.1% by weight are listed as carcinogens by IARC, NTP or OSHA

SECTION 3- PHYSICAL DATA

Boiling Point: 212°F
Vapor Pressure: 17 mm @ 20° C
% Volatile: 85%
Solubility in Water: Emulsion
Physical Description: Milky White Liquid, Characteristic Odor

Specific Gravity: 1.010 – 1.030
Vapor Density (Air=1): >1
pH: 8.0 – 9.0
Evaporation Rate (Water=1): >1

SECTION 4- FIRE AND EXPLOSION HAZARD DATA

Flash Point: None
Extinguishing Media: Product will not burn.
Special Firefighting Procedures: Keep drums cool to prevent vapor rupture.
Unusual Fire and Explosion Hazards: N.A.
Upper Explosion Limits: N.A. **Lower Explosion Limits:** N.A.

SECTION 5- REACTIVITY DATA

Stability: Stable
Hazard Decomposition Products: Thermal: CO; CO₂

Hazardous Polymerization: Will not occur
Incompatibility (Materials to Avoid): Strong oxidizers; mineral acids.

SECTION 6- STORAGE AND HANDLING INFORMATION

Keep container closed when not in use. Protect container from abuse. Protect from extreme temperatures.

SECTION 7- HEALTH HAZARDS AND FIRST AID

Effects of Overexposure
Skin: slight irritation; prolonged contact may cause moderate reddening, swelling and burning.
Eyes: severe irritation and pain associated with redness and swelling of conjunctiva.
Inhalation: irritating to respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.
Ingestion: moderately toxic; may cause headache, dizziness, diarrhea, and general weakness; large doses may result in red blood cell hemolysis.
First Aid Procedures
Skin: remove contaminated clothing, wash skin thoroughly with water.
Eyes: flush with water for 15 minutes; seek medical attention.
Inhalation: remove to fresh air; if symptoms persist seek medical attention.
Ingestion: give 2 glasses water; induce vomiting in conscious person; seek medical attention.

SECTION 8- SPECIAL PROTECTION INFORMATION

Respiratory Protection: none required below threshold limits.
Ventilation Requirements: recommended
Protective Gloves: recommended
Eye Protection: goggles with side shields
Other Protective Equipment: safety eyebath nearby

SECTION 9-SPILL OR LEAK PROCEDURES

Cleanup Procedure for Spills: Confine and absorb into approved absorbent; place material in approved containers for disposal. Refer to SARA Title III, Section 313, refer to 40 CFR 372. For spills in excess of allowable limits, refer to CERCLA 40 CFR 302 for reporting requirements.
Waste Disposal: Refer to RCRA regulations 40 CFR 260 – 281 for waste disposal instructions. **DO NOT FLUSH to sanitary sewer or waterway.**

SECTION 10-REGULATORY INFORMATION

SARA Title III – Section 311/312 – Hazard: (Y/N): Y
Fire: N
Sudden Release of Pressure: Y
Reactivity: N
Acute (IMMEDIATE) Health Hazard: slight irritation
Chronic (DELAYED) Health Hazard: N
Other: Keep this and other chemicals out of reach of children. Minimize body contact with this product as all chemicals in general.

Shipping Information
Shipping name: Floor Polish
Hazard class: none
Reference: 49 CFR 172.101
ID #: none
Label: none

HMIS Hazardous Material Identification System

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

For **emergency** and **medical** help line, call **INFOTRAC** at **1-800-535-5053**, 24 hours a day, 7 days a week for information on all our products and/or MSDS. Obtain an MSDS at www.pride-enterprises.org/MSDS/menu.htm or call customer service at **(813)-890-6594**

SECTION 11- OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts No responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept NO liability for damages or loss incurred from the improper handling and use of this product.