



Spray Buff Solution

FLOOR CARE PRODUCTS

DESCRIPTION: Brilliant's **Spray Buff Solution** is a ready – to – use floor polish designed to renew the shine between waxing of **Brilliant's Glossy Finish I or II** or any other brand floor polish. This product requires a minimum of effort and time to brighten dull and worn high traffic areas. When used with **Brilliant's** floor finishes this product adds extra hardness.

DIRECTIONS:

- Locate dull areas on the floor that have lost their shine.
- Do not apply **Brilliant's Spray Buff Solution** over dirty or badly scuffed floors. Very dirty floors should be cleaned with **Brilliant's Multi-Cleaner**. Repairing moderate to light scuffmarks is the specialty of this product.
- Use a spray bottle of **Brilliant's Spray Buff Solution** at full strength to apply a moderate amount – enough to moisten area – onto dull areas.
- Use a power buffer to restore the original shine to treated areas. For best results, use a red or white buffer pad.

PACKAGING:

SIZE

12/1 quart case
4/1 gallon jugs
55 gallon barrel

CATALOG #

64600512
64600504
64600555

PRODUCT SPECIFICATIONS

Appearance:	White, milky liquid
Odor:	Characteristic
Solids content:	5 - 6%
Viscosity:	<10
Specific gravity:	1.000 – 1.020
pH:	8.0 – 9.0

Detergent resistant to SURECLEAN'S MULTI-PURPOSE CLEANER at 2.5 oz./ gal. dilution applied on vinyl black composite tile: Less than 10% deterioration after 60 strokes (ASTM 3207-73).

ISO 9001:2000 Certified
Certificate No. 2049



EAGLE Registrations Inc.
SERVICE • INTEGRITY • VALUE

BRILLIANT PRODUCTS
P. O. Box 1425 Avon Park, FL 33826
Phone: 813-890-6594 Fax: 813-890-2101



CONTROLLED

Issue Date: 05/15/08
Form PB646005B, Rev (E)

MATERIAL SAFETY DATA SHEET

Prepared By: D. Wilson

(Prepared According to 29 CFR 1910.1200)

Effective Date: 08/10/05

SECTION 1- PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: SPRAY BUFF SOLUTION Generic Name: Acrylic Floor Finish Product Group: Floor Care Products	Manufacturer's Name: BRILLIANT PRODUCTS P.O. BOX 1425 AVON PARK, FL 33826 Phone #: (813)-890-6594
--	--

SECTION 2- INGREDIENT INFORMATION

CHEMICAL NAME	CAS #	WT %	PEL	TWA-TLV	STEL-TLV
Diethylene Glycol Methyl Ether	111-77-3	<5	N.A.	10/ m ³	N.A.

No Components, in excess of 0.1% by weight are listed as carcinogens by IARC, NTP or OSHA

SECTION 3- PHYSICAL DATA

SECTION 4- FIRE AND EXPLOSION HAZARD DATA

Boiling Point: 212°F Vapor Pressure: 17 mm @ 20° C % Volatile: 94% Solubility in Water: Emulsion Physical Description: Milky White Liquid, Characteristic Odor	Specific Gravity: 1.000 – 1.020 Vapor Density (Air=1): <1 pH: 8.0 – 9.0 Evaporation Rate (Water=1): >1	Flash Point: None Extinguishing Media: Product will not burn. Special Firefighting Procedures: Keep drums cool to prevent vapor rupture. Unusual Fire and Explosion Hazards: N.A. Upper Explosion Limits: N.A. Lower Explosion Limits: N.A.
---	---	---

SECTION 5- REACTIVITY DATA

Stability: Stable Hazard Decomposition Products: Thermal: CO; CO ₂	Hazardous Polymerization: Will not occur Incompatibility (Materials to Avoid): Strong oxidizers; mineral acids.
--	--

SECTION 6- STORAGE AND HANDLING INFORMATION

Keep container closed when not in use. Protect container from abuse. Protect from extreme temperatures.

SECTION 7- HEALTH HAZARDS AND FIRST AID

SECTION 8- SPECIAL PROTECTION INFORMATION

Effects of Overexposure
Skin: slight irritation; prolonged contact may cause moderate reddening, swelling and burning.
Eyes: severe irritation and pain associated with redness and swelling of conjunctiva.
Inhalation: irritating to respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.
Ingestion: moderately toxic; may cause headache, dizziness, diarrhea, and general weakness; large doses may result in red blood cell hemolysis.
First Aid Procedures
Skin: remove contaminated clothing, wash skin thoroughly with water.
Eyes: flush with water for 15 minutes; seek medical attention.
Inhalation: remove to fresh air; if symptoms persist seek medical attention.
Ingestion: give 2 glasses water; induce vomiting in conscious person; seek medical attention.

Respiratory Protection: none required below threshold limits.
Ventilation Requirements: recommended
Protective Gloves: recommended
Eye Protection: goggles with side shields
Other Protective Equipment: safety eyebath nearby

SECTION 9-SPILL OR LEAK PROCEDURES

Cleanup Procedure for Spills: Confine and absorb into approved absorbent; place material in approved containers for disposal. Refer to SARA Title III, Section 313, refer to 40 CFR 372. For spills in excess of allowable limits, refer to CERCLA 40 CFR 302 for reporting requirements.
Waste Disposal: Refer to RCRA regulations 40 CFR 260 – 281 for waste disposal instructions. **DO NOT FLUSH to sanitary sewer or waterway.**

SECTION 10-REGULATORY INFORMATION

SARA Title III – Section 311/312 – Hazard: (Y/N): Fire: N Sudden Release of Pressure: Y Reactivity: N Acute (IMMEDIATE) Health Hazard: N Chronic (DELAYED) Health Hazard: N Other: Keep this and other chemicals out of reach of children. Minimize body contact with this product as all chemicals in general.	Shipping Information Shipping name: Floor Polish Hazard class: none Reference: 49 CFR 172.101 ID #: none Label: none	HMIS Hazardous Material Identification System	
		Health	1
		Flammability	0
		Reactivity	0
For emergency and medical help line, call INFOTRAC at 1-800-535-5053 , 24 hours a day, 7 days a week for information on all our products and/or MSDS. Obtain an MSDS at www.pride-enterprises.org/MSDS/menu.htm or call customer service at (813)-890-6594		Personal Protection	B

SECTION 11- OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts No responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept NO liability for damages or loss incurred from the improper handling and use of this product.