



Heavy Duty Pro Waxx Away

NON-AMMONIATED FLOOR STRIPPER

FLOOR CARE PRODUCTS

DESCRIPTION: PRIDE's Heavy Duty Pro Waxx Away is a very fast acting and concentrated, non-ammoniated floor stripper designed to remove PRIDE's Gloss Pro I or II or any brand floor wax including metal-interlocking polymer finishes. When applied to waxed surface, Heavy Duty Pro Waxx Away begins to react as quickly as 30 seconds! This product can be used on vinyl, asphalt tile, rubber, terrazzo, linoleum, cork, and concrete floors.

DIRECTIONS:

- Depending on build-up, dilute Heavy Duty Pro Waxx Away from 1:1 to 1:5 with hot water.
- Mop floors with mix solution freely. Allow to stand 5-10 minutes (when wax is seen to dissolve).
- Never use strip mop for any other application or purpose.
- Rinse at least twice with clean water.
- Let floor dry completely before applying PRIDE's Pro Seal Brite or PRIDE's Gloss Pro I or Gloss Pro II.

PACKAGING:

<u>SIZE</u>	<u>CATALOG #</u>
4/1 gallon case	64600904
5 gallon pail	64600905
30 gallon drum	64600930
55 gallon barrel	64600955

PRODUCT SPECIFICATIONS

Appearance:	Clear Liquid
Color:	Purple
Odor:	Solvent
pH:	10.5 - 12.5
Specific Gravity:	.930 - 1.012
Viscosity:	<10

ISO 9001:2000 Certified
Certificate No. 2049



EAGLE Registrations Inc.
SERVICE • INTEGRITY • VALUE

PRIDE ENTERPRISES

P. O. Box 1425 Avon Park, FL 33826
Phone: 813-890-6594 Fax: 813-890-2101 www.pride-enterprises.org



CONTROLLED

Issue Date: 05/09/08
Form PB646009, Rev (H)

MATERIAL SAFETY DATA SHEET

Prepared By: Manny Cueto

(Prepared According to 29 CFR 1910.1200)

Effective Date: 08/10/05

SECTION 1- PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: HEAVY DUTY PRO WAXX AWAY
Generic Name: Stripper
Product Group: Floor Care Products

Manufacturer's Name: SANITARY MAINTENANCE & SUPPLY
 P.O. BOX 1425
 AVON PARK, FL 33826
Phone #: (813)-890-6594

SECTION 2- INGREDIENT INFORMATION

CHEMICAL NAME	CAS #	WT %	PEL	TWA-TLV	STEL-TLV
Ethylene Glycol Monobutyl Ether	111-76-2	N.A.	N.A.	121 mg/mm ³	N.A.
Monoethanolamine	141-43-5	N.A.	N.A.	7.5 mg/mm ³	15 mg/mm ³

No Components, in excess of 0.1% by weight are listed as carcinogens by IARC, NTP or OSHA

SECTION 3- PHYSICAL DATA

Boiling Point: 212°F
Vapor Pressure: 17 mm @ 20° C
% Volatile: 96%
Solubility in Water: complete
Physical Description: clear purple liquid, solvent odor

Specific Gravity: .930 - 1.012
Vapor Density (Air=1): >1
pH: 10.5 – 12.5
Evaporation Rate (Water=1): >1

SECTION 4- FIRE AND EXPLOSION HAZARD DATA

Flash Point: None
Extinguishing Media: water fog, CO₂
Special Firefighting Procedures: Keep drums cool to prevent vapor rupture.
Unusual Fire and Explosion Hazards: N.A.
Upper Explosion Limits: N.A. **Lower Explosion Limits:** N.A.

SECTION 5- REACTIVITY DATA

Stability: Stable
Hazard Decomposition Products: Thermal: CO; CO₂

Hazardous Polymerization: Will not occur
Incompatibility (Materials to Avoid): Strong oxidizers; mineral acids.

SECTION 6- STORAGE AND HANDLING INFORMATION

Keep container closed when not in use. Protect container from abuse. Protect from extreme temperatures.

SECTION 7- HEALTH HAZARDS AND FIRST AID

Effects of Overexposure
Skin: brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and burning.
Eyes: severe irritation and pain associated with redness and swelling of conjunctiva.
Inhalation: irritating to respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.
Ingestion: moderately toxic; may cause headache, dizziness, diarrhea, and general weakness; large doses may result in red blood cell hemolysis.
First Aid Procedures
Skin: remove contaminated clothing, wash skin thoroughly with water.
Eyes: flush with water for 15 minutes; seek medical attention.
Inhalation: remove to fresh air; if symptoms persist seek medical attention.
Ingestion: give 2 glasses water; induce vomiting in conscious person; seek medical attention.

SECTION 8- SPECIAL PROTECTION INFORMATION

Respiratory Protection: none required below threshold limits.
Ventilation Requirements: recommended
Protective Gloves: recommended
Eye Protection: goggles with side shields
Other Protective Equipment: safety eyebath nearby

SECTION 9- SPILL OR LEAK PROCEDURES

Cleanup Procedure for Spills: Confine and absorb into approved absorbent; place material in approved containers for disposal. Refer to SARA Title III, Section 313, refer to 40 CFR 372. For spills in excess of allowable limits, refer to CERCLA 40 CFR 302 for reporting requirements.
Waste Disposal: Dispose in accordance with local, state and federal regulations.

SECTION 10- REGULATORY INFORMATION

SARA Title III – Section 311/312 – Hazard: (Y/N): Y
Fire: N
Sudden Release of Pressure: Y
Reactivity: N
Acute (IMMEDIATE) Health Hazard: slight irritation
Chronic (DELAYED) Health Hazard: May aggravate pre-existing skin, eye or respiratory conditions with long term exposure.
Other: Keep this and other chemicals out of reach of children. Minimize body contact with this product as all chemicals in general.

Shipping Information
Shipping name: Corrosive Liquids, basic, inorganic, nos
Hazard class: 8
Reference: 49 CFR 172.101
ID #: UN 3266
Label: corrosive

HMIS Hazardous Material Identification System

Health	2
Flammability	1
Reactivity	0
Personal Protection	B

For **emergency** and **medical** help line, call **INFOTRAC** at **1-800-535-5053**, 24 hours a day, 7 days a week for information on all our products and/or MSDS. Obtain an MSDS at www.pride-enterprises.org/MSDS/menu.htm or call customer service at **(813)-890-6594**

SECTION 11- OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts No responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept NO liability for damages or loss incurred from the improper handling and use of this product.