



# Solvent Wood Floor Cleaner

## WATERLESS SOLVENT WOOD FLOOR CLEANER

### WOOD CARE PRODUCTS

**DESCRIPTION:** Solvent Wood Floor Cleaner is a blend of refined solvents formulate for use in cleaning and preparing wood, concrete, terrazzo, quarry tile, and other hard surfaces prior to sealing and/or finishing. Easily removes most dirt, soil, oil, black heel marks, rubber burns, chewing gum and tar. Excellent for tack ragging wood, and as a cleanup solvent for application tools. Designed to evaporate quickly, leaving no greasy or oily residue to damage gloss and/or prevent bonding. Not for use on resilient tile.

**DIRECTIONS:** In federally inspected meat and poultry plants, equipment must be washed with an effective cleaner and rinsed with potable water.

- *For use on wood floors prior to coating:* Apply with a mop and bucket to areas of approximately 100 square feet. Immediately scrub with a scrubbing pad or steel wool. Pick up with a wet vacuum or mop. Rinse floor thoroughly with fresh product and allow one hour dry time before to coating.
- *For tacking of floors:* Apply to clean cotton towels, making sure not to over-wet. Tack in the usual manner.
- *For removing tar, rubber burns, chewing gum, etc.:* Apply to a clean cotton cloth. Rub soiled area until clean. Apply directly to larger areas of soila or rubber burns and allow to soak for several minutes before wiping clean.
- *For parts and machinery cleaning:* Spray product directly from container and wipe dry. Immerse parts to be cleaned in solution. Wipe or air dry.

<b>PACKAGING:</b>	<u>SIZE</u> 2/2.5 gallon case	<u>CATALOG #</u> 64601305
-------------------	----------------------------------	------------------------------

#### PRODUCT SPECIFICATIONS

<b>Active Ingredients:</b>	100%	<b>Drying Time:</b>	rapid
<b>Color:</b>	clear	<b>Flash Point:</b>	106° F (TCC)
<b>Odor:</b>	solvent	<b>Storage/Stability:</b>	2 years
<b>Solvent System:</b>	high K.B. mineral spirits	<b>Weight per Gallon:</b>	6.87 lbs
<b>Viscosity:</b>	water thin	<b>Freeze/ Thaw Stability:</b>	keep from freezing
<b>Foam:</b>	low	<b>Coverage:</b>	300-400 ft <sup>2</sup> /gallon
<b>Water Miscibility:</b>	none		
<b>Sediment:</b>	none		

ISO 9001:2000 Certified  
Certificate No. 2049



**EAGLE Registrations Inc.**  
SERVICE • INTEGRITY • VALUE

#### PRIDE ENTERPRISES

P. O. Box 1425 Avon Park, FL 33826

Phone: 813-890-6594 Fax: 813-890-2101 www.pride-enterprises.org



CONTROLLED

Issue Date: 05/30/08  
Form PB64601305, Rev (F)

**MATERIAL SAFETY DATA SHEET**

Prepared By: M. Cueto

(Prepared According to 29 CFR 1910.1200)

Effective Date: 08/10/05

**SECTION 1- PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION**

<b>Product Name:</b> SOLVENT WOOD FLOOR CLEANER <b>Generic Name:</b> Waterless cleaner <b>Product Group:</b> Wood Floor Care	<b>Supplier's Name:</b> SANITARY MAINTENANCE & SUPPLY P.O. BOX 1425 AVON PARK, FL 33826 <b>Phone #:</b> (813)-890-6594
--	---

**SECTION 2- INGREDIENT INFORMATION**

CHEMICAL NAME	CAS #	WT %	PEL	TWA-TLV	STEL-TLV
Petroleum Distillates	64742-48-9	45 to 55	500 ppm	100 ppm	N/A.
Aromatic Hydrocarbons	64742-95-6	45 to 55	500 ppm	50 ppm	N/A.

**SECTION 3- PHYSICAL DATA**

**SECTION 4- FIRE AND EXPLOSION HAZARD DATA**

<b>Boiling Point:</b> 310° F Initial <b>Vapor Pressure:</b> <10mm Hg @ 68° F <b>% Volatile:</b> 100% <b>Solubility in Water:</b> Nil <b>Physical Description:</b> Thin colorless liquid with characteristic odor	<b>Specific Gravity:</b> .83 <b>Vapor Density (Air=1):</b> >1 <b>pH:</b> N/A. <b>Evaporation Rate (Water=1):</b> >1	<b>Flash Point:</b> 106° F (TCC). <b>Extinguishing Media:</b> Foam, CO <sub>2</sub> , dry chemical <b>Special Firefighting Procedures:</b> DO NOT use water <b>Unusual Fire and Explosion Hazards:</b> Heated drums can explode <b>Upper Explosion Limits:</b> 6 <b>Lower Explosion Limits:</b> 7
--	--	---

**SECTION 5- REACTIVITY DATA**

<b>Stability:</b> Stable <b>Hazard Decomposition Products:</b> Carbon monoxide possible if burned	<b>Incompatibility (Materials to Avoid):</b> Strong oxidizers <b>Hazardous Polymerization:</b> None
--	--

**SECTION 6- STORAGE AND HANDLING INFORMATION**

Keep out of reach of children. Combustible liquid. Avoid contact with excessive heat, spark or open flame. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For industrial and institutional use only. Avoid contact with eyes, skin and clothing. Avoid breathing mist or vapors. Use in well ventilated area. Empty container may contain explosive or flammable vapors.

**SECTION 7- HEALTH HAZARDS AND FIRST AID**

**SECTION 8- SPECIAL PROTECTION INFORMATION**

**Effects of Overexposure**  
**Skin:** Prolonged or repeated contact may cause irritation, defatting of skin leading to dermatitis.  
**Eyes:** Eye irritant. May cause redness, swelling or blurred vision.  
**Inhalation:** High concentration and/or long term exposure may irritate mucous membranes of the respiratory tract. Headaches, dizziness and nausea, as well as unconsciousness may result from overexposure to high concentrations over extended periods.  
**Ingestion:** Liquid ingestions may result in vomiting. Aspiration of material into the lungs can cause pneumonitis and pulmonary edema/hemorrhage.  
**First Aid Procedures**  
**Skin:** Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists.  
**Eyes:** Flush with large quantities of water, holding eyes open. Seek medical attention.  
**Inhalation:** Get to fresh air. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist.  
**Ingestion: DO NOT INDUCE VOMITING, DO NOT GIVE LIQUIDS.** Seek medical attention immediately.

**Respiratory Protection:** Use with adequate ventilation. Use NIOSH approved Hydrocarbon (organic vapor) canister respirator when using in confined areas.  
**Ventilation Requirements:** provide explosion-proof ventilation to keep TLV of Section 2 ingredients below acceptable limits.  
**Protective Gloves:** solvent-proof neoprene or viton.  
**Eye Protection:** Chemical splash goggles or full-face shield.  
**Other Protective Equipment:** Spark resistant tools are recommended. Eye-wash & Fire extinguisher nearby. Full protective outerwear and chemical resistant footwear when using.

**SECTION 9-SPILL OR LEAK PROCEDURES**

**Cleanup Procedure for Spills:** Shut off all ignition sources and ventilate area. Floors will become slippery. Dike or contain liquid. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways  
**Waste Disposal:** Any method in accordance with local, state, and federal laws. Best method is to recycle or reuse for intended purposes. If discarded, this material and containers should be treated as hazardous waste based on the characteristics of ignitability as defined under federal RCRA regulations (40 CFR 261). Do not dispose of into storm drain, stream, river, or to ground. Rinse container thoroughly before discarding in trash. Rinse containers thoroughly before discarding in trash. Consult local or state environmental officials for further information.

**SECTION 10-REGULATORY INFORMATION**

<b>SARA Title III – Section 311/312 – Hazard: (Y/N):</b> <b>Fire:</b> Y <b>Sudden Release of Pressure:</b> N <b>Reactivity:</b> N <b>Acute (IMMEDIATE) Health Hazard:</b> Y <b>Chronic (DELAYED) Health Hazard:</b> Y <b>Other:</b> N/A	<b>Shipping Information</b> <b>Shipping Name:</b> Containers > 1 gallon: cleaning compound  Container 1 gallon: cleaning compound  Container < 1 gallon: cleaning compound	<b>HMIS Hazardous Material Identification System</b>	
		<b>Health</b>	<b>2</b>
		<b>Flammability</b>	<b>2</b>
		<b>Reactivity</b>	<b>0</b>
	For <b>emergency</b> and <b>medical</b> help line, call <b>INFOTRAC</b> at <b>1-800-535-5053</b> , 24 hours a day, 7 days a week for information on all our products and/or MSDS. Obtain an MSDS at <a href="http://www.pride-enterprises.org/MSDS/menu.htm">www.pride-enterprises.org/MSDS/menu.htm</a> or call customer service at <b>(813)-890-6594</b>		<b>Personal Protection</b>

**SECTION 11- OTHER INFORMATION**

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts No responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept NO liability for damages or loss incurred from the improper handling and use of this product.