



Gloss Pro IV

PREMIUM FLOOR FINISH

FLOOR CARE PRODUCTS

DESCRIPTION: Pride's Gloss Pro IV is a premium grade, non-yellowing acrylic floor wax finish based on 36% solids for a superior gloss. Will impart a very tough black-mark resistant film, unaffected by multiple detergent scrubbing. Can be re-coated to blend with previous applications, eliminating the need for frequent stripping. Use on all types of floors: vinyl, vinyl asbestos, asphalt tile, rubber tile, terrazzo, and linoleum.

DIRECTIONS:

- Strip floor for initial coat using **Pride's H.D. Pro Waxx-Away**, with special attention to areas near baseboards, under desks, etc.
- Rinse completely with clean water and allow to dry thoroughly.
- Apply even coat of wax using a clean mop or applicator. Allow to dry for 20 minutes, and then apply second coat. Mop or applicator should be used for wax only and never return unused wax to original container.
- Maintenance is easy: Wet-mop floors weekly or as needed for high traffic areas using non-ammoniated detergent diluted for normal cleaning. For heavy soil, a stronger dilution of cleaner will not affect finish.
- Use **Pride's Buff Pro** between waxing to maintain a high gloss.
- Re-coating: Apply a single coat of **Gloss Pro IV** to cleaned and dried area.
- When removal of finish is necessary, **Pride's H.D. Pro Waxx-Away** will easily strip finish with minimal effort.

PACKAGING:

SIZE

4/1 gallon Case
5 gallon Pail
15 gallon drum
55 gallon Barrel

CATALOG

64602004
64602005
64602015
64602055

PRODUCT SPECIFICATIONS

| | |
|-------------------|----------------|
| Appearance: | Milky liquid |
| Color: | White |
| Odor: | Characteristic |
| pH: | 8.0-9.0 |
| Specific gravity: | 1.030 - 1.060 |
| Viscosity: | <10 |
| Solids content: | 36% |

ISO 9001:2000 Certified
Certificate No. 2049



EAGLE Registrations Inc.
SERVICE • INTEGRITY • VALUE

PRIDE ENTERPRISES
P. O. Box 1425 Avon Park, FL 33826
Phone: 813-890-6594 Fax: 813-890-2101 www.pride-enterprises.org



CONTROLLED

Issue Date: 05/09/08
Form PB646020, Rev (H)

MATERIAL SAFETY DATA SHEET

Prepared By: Manny Cueto

(Prepared According to 29 CFR 1910.1200)

Effective Date: 08/10/05

SECTION 1- PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: GLOSS PRO IV
Generic Name: Acrylic Floor Finish
Product Group: Floor Care Products

Manufacturer's Name: SANITARY MAINTENANCE & SUPPLY
 P.O. BOX 1425
 AVON PARK, FL 33826
Phone #: (813)-890-6594

SECTION 2- INGREDIENT INFORMATION

| CHEMICAL NAME | CAS # | WT % | PEL | TWA-TLV | STEL-TLV |
|--------------------------------|----------|------|------|---------|----------|
| Diethylene Glycol Methyl Ether | 111-77-3 | N.A. | N.A. | N.A. | N.A. |
| Dibutyl Phthalate | 87-74-2 | N.A. | N.A. | N.A. | N.A. |

No Components, in excess of 0.1% by weight are listed as carcinogens by IARC, NTP or OSHA

SECTION 3- PHYSICAL DATA

Boiling Point: 212°F
Vapor Pressure: 17 mm @ 20° C
% Volatile: 90%
Solubility in Water: Emulsion
Physical Description: Milky White Liquid, Characteristic Odor

Specific Gravity: 1.030 - 1.060
Vapor Density (Air=1): >1
pH: 8.0 – 9.0
Evaporation Rate (Water=1): <1

SECTION 4- FIRE AND EXPLOSION HAZARD DATA

Flash Point: None
Extinguishing Media: Product will not burn.
Special Firefighting Procedures: Keep drums cool to prevent vapor rupture.
Unusual Fire and Explosion Hazards: N.A.
Upper Explosion Limits: N.A. **Lower Explosion Limits:** N.A.

SECTION 5- REACTIVITY DATA

Stability: Stable
Hazard Decomposition Products: Thermal: CO; CO₂, phosphorous fumes.

Hazardous Polymerization: Will not occur
Incompatibility (Materials to Avoid): Strong oxidizers; mineral acids.

SECTION 6- STORAGE AND HANDLING INFORMATION

Keep container closed when not in use. Protect container from abuse. Protect from extreme temperatures.

SECTION 7- HEALTH HAZARDS AND FIRST AID

Effects of Overexposure
Skin: brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and burning.
Eyes: severe irritation and pain associated with redness and swelling of conjunctiva.
Inhalation: irritating to respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.
Ingestion: moderately toxic; may cause headache, dizziness, diarrhea, and general weakness; large doses may result in red blood cell hemolysis.
First Aid Procedures
Skin: remove contaminated clothing, wash skin thoroughly with water.
Eyes: flush with water for 15 minutes; seek medical attention.
Inhalation: remove to fresh air; if symptoms persist seek medical attention.
Ingestion: give 2 glasses water; induce vomiting in conscious person; seek medical attention.

SECTION 8- SPECIAL PROTECTION INFORMATION

Respiratory Protection: none required below threshold limits.
Ventilation Requirements: recommended
Protective Gloves: recommended
Eye Protection: goggles with side shields
Other Protective Equipment: safety eyebath nearby

SECTION 9-SPILL OR LEAK PROCEDURES

Cleanup Procedure for Spills: Confine and absorb into approved absorbent; place material in approved containers for disposal. Refer to SARA Title III, Section 313, refer to 40 CFR 372. For spills in excess of allowable limits, refer to CERCLA 40 CFR 302 for reporting requirements.
Waste Disposal: Dispose in accordance with local, state and federal regulations.

SECTION 10-REGULATORY INFORMATION

SARA Title III – Section 311/312 – Hazard: (Y/N):
Fire: N
Sudden Release of Pressure: Y
Reactivity: N
Acute (IMMEDIATE) Health Hazard: N
Chronic (DELAYED) Health Hazard: N
Other: Keep this and other chemicals out of reach of children. Minimize body contact with this product as all chemicals in general.

Shipping Information
Shipping name: Floor Polish
Hazard class: None
Reference: 49 CFR 172.101
ID #: None
Label: None

HMIS Hazardous Material Identification System

| | |
|----------------------------|----------|
| Health | 1 |
| Flammability | 1 |
| Reactivity | 0 |
| Personal Protection | B |

For **emergency** and **medical** help line, call **INFOTRAC** at **1-800-535-5053**, 24 hours a day, 7 days a week for information on all our products and/or MSDS. Obtain an MSDS at www.pride-enterprises.org/MSDS/menu.htm or call customer service at **(813)-890-6594**

SECTION 11- OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts No responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept NO liability for damages or loss incurred from the improper handling and use of this product.